



Product Specification Report

1.0/06400007/0725

Provides the surface with a smooth, clear satin 'matte' finish. Stains and streaks are a thing of the past. Deoxidises and cleans aluminium in a single treatment.

BRITE STALUME 27

Cleaner and gloss restorer for aluminium surfaces

FEATURES:

Concentrated	A particularly fast-acting concentrated liquid for cleaning aluminium.
Restorative	Cleans and restores gloss immediately upon contact with the surface to be cleaned.
Versatile	Suitable for use on aluminium, lorries, trailers, petrol stations, livestock transport, laundries, and cladding.
Anti-glare	Brite Stalume 27 provides the surface with a smooth, clear satin 'matte' finish, preventing dangerous glare on lorries or trailers.
Fast-acting	The product works quickly and effectively. The results are immediately visible.
Spotless	Stains and streaks become a thing of the past.
Aluminium deoxidation	Deoxidises aluminium in a single treatment.
Concentrated	Highly concentrated.

INSTRUCTIONS FOR USE:

- In most cases, dilute 1 part product with 3 parts water. On warm days, dilute 1 part product with 10 parts water.
- Apply the solution using a sprayer, working from the bottom upwards.
- Allow the solution to work for a few minutes, then rinse thoroughly with plenty of water.
- If stubborn corrosion requires further treatment, a soft brush or cotton mop is the best tool to use.
- Make sure to rinse the sprayer with water after use.

SPECIFICATIONS:

Type Degreaser and etching agent for aluminium
Colour Clear, colourless liquid
Odour Sharp and penetrating
PH < 1
Density $\pm 1,08 \text{ g/cm}^3$
Flammability Non-flammable

PRECAUTIONS FOR USE:

When treating a lorry, first wet all windows thoroughly with plenty of water. Do not use on anodised aluminium.

All information in this document is based on our practical experience and/or laboratory tests. Due to the multiplicity of conditions for usage and variable human factors, we recommend that you always test our products for suitability prior to use. At any time, this version of the product specification report may have been revised based on legislation, availability of the individual ingredients or newly acquired information. The current approved version is available upon request.



Zep UK Ltd.
T • 0151 422 1000
F • 0151 422 1011
info@zep.co.uk
www.zep.co.uk



Zep Italia s.r.l.
T • 800 016 918
Numero Verde Tecnico
800-579185
tecnico@zepeurope.com
www.zep.it



Zep Industries BV
T • 02 347 01 17
F • 02 347 13 95
sales@zep.be
www.zepindustries.be



Zep Industries BV
T • 0164 250100
F • 0164 266710
info@zepbenelux.com
www.zepindustries.nl



Zep Industries BV
T • 0521 174158
F • 0521 5217114
sales@zepbenelux.com
www.zepindustries.de